

# FAST SET CONCRETE PATCH PRODUCT DATA SHEET

## DESCRIPTION

**Enviro Epoxy's Fast Set Concrete Patch (FSC)** is a complete, ready-to-use concrete patching compound that is unequalled for fast, permanent repairs. It sets faster (less than 45 minutes), has high compressive strength (9,000 - 10,000 psi), and a greater bonding power than any other patching material available.

Enviro Epoxy's Fast Set Concrete Patch is an environmentally friendly product and CFIA approved.

## RECOMMENDED USES

Repair of bridges, tunnels, concrete roads, parking lots, sidewalks, concrete floors, and industrial structures.

## SURFACE PREPARATION

**Fast Set Concrete Patch** should be applied on clean, sound surfaces, free of oily film. Scaling and/or unsound concrete should be chipped out and cleared to provide a firm base. Soak the area(s) to be repaired with water. Just prior to application, sweep out all puddles to provide a uniformly moist surface.

## WATER RATIO

Use 4 pints (1.9lt) of clean water for 44lb of **Enviro Epoxy Fast Set Concrete Patch**. **THE EXACT AMOUNT OF WATER IS VERY IMPORTANT.**

## MIXING

Weigh and place the dry powder in a clean container. Add water gradually and mix thoroughly for 2-3 minutes. **DO NOT MIX MORE THAN 4 MINUTES** due to this product's fast setting time and high exotherm.

Note: Mixing and application of each batch should be completed in 10 minutes or less.

## APPLICATION

Smoothing should be done while the cement is still wet. Use a trowel or metal float held flat. Make sure the area is as smooth as possible during the application. Repaired areas are ready for traffic in 45 minutes.

## COVERAGE

One 44lb kit covers 17.6 sqft at ¼" thick.

## STORAGE

Keep container closed as material is moisture sensitive.



Enviro Epoxy Products Inc. warrants this product to be free of defects in accordance with Enviro Epoxy Products Inc. quality control procedures. Liability for products proven defective is limited to replacement of product purchased or refund of the purchase price paid. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY Enviro Epoxy Products Inc., EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.